

				CLUTCH DIMENSIONS			REMARKS		
DAF									
LF 45									
45.170	-01.01	BE 123C	ZF 5S-42	362 x 38.1 - 10 (Pre- Damper)	71/2-63011	81/2-7138	CV=Pressed Steel CT=Push CL=Single D/L=Diaphragm FLW =Flat	RBRG-000-395 With Collar	830/840-1156
45.150 45.170 45.180 45.220	01.01- 01.01- 01.01- 01.01-	BE 110C BE 123C CE 136C CE 162C	ZF 5S-42	362 x 38.1 - 10 (Pre- Damper)	71/2-63011	81/2-7138	CV=Pressed Steel CT=Push CL=Single D/L=Diaphragm FLW =Flat	RBRG-000-002 With Collar	830/840-1155
			ZF 6S-850	395 x 38.1 - 10 (Pre- Damper)	71/2-63012	81/2-7139	CV=Pressed Steel CT=Push CL=Single D/L=Diaphragm FLW =Flat	RBRG-000-395 With Collar	830/840-1213
LF 55									
55.170	-01.01	BE 123C	ZF 6S-850	362 x 38.1 - 10 (Pre- Damper)	71/2-63011	81/2-7138	CV=Pressed Steel CT=Push CL=Single D/L=Diaphragm FLW =Flat	RBRG-000-395 With Collar	830/840-1156
55.170 55.180 55.220 55.250	01.01- 01.01- 01.01- 01.01-	BE 123C CE 136C CE 162C CE 184C	ZF 6S-850	395 x 38.1 - 10 (Pre- Damper)	71/2-63012	81/2-7139	CV=Pressed Steel CT=Push CL=Single D/L=Diaphragm FLW =Flat	RBRG-000-395 With Collar	830/840-1213
			Eaton	395 x 44.5 - 10 (Pre- Damper)	71/2-63032	81/2-7139	CV=Pressed Steel CT=Push CL=Single D/L=Diaphragm FLW =Flat	RBRG-000-395 With Collar	830/840-1214
55.210	01.93-	Cummins B Series	ZF 9S75	380 x 44.5 - 10	71/2-61013	81/2-7172	CV=Cast Iron CT=Push CL=Single D/L=Diaphragm FLW =Flat	RBRG-007-303 With Collar	830/840-1176
55.220 55.250 55.290	05.06 - 05.06 - 05.06 -	GR 165S1 GR 184S1 GR 210S1	-	395 x 44.5 - 10 (Pre- Damper)	71/2-63032	81/2-7139	CV=Pressed Steel CT=Push CL=Single D/L=Diaphragm FLW =Flat	-	-
65 CF									
65 CF 180 65 CF 210 65 CF 240	02.98-12.00 02.98-12.00 02.98-12.00	NS 133M NS 156M NS 177M	-	362 x 38.1 - 10 (Pre- Damper)	71/2-63011	81/2-7138	CV=Pressed Steel CT=Push CL=Single D/L=Diaphragm FLW =Flat	RBRG-000-395 With Collar	830/840-1156
CF 65									
65.180 65.220 65.250	01.01- 01.01- 01.01-	CE 136C CE 162C CE 184C	ZF 6S-850	395 x 38.1 - 10 (Pre- Damper)	71/2-63012	81/2-7139	CV=Pressed Steel CT=Push CL=Single D/L=Diaphragm FLW =Flat	RBRG-000-395 With Collar	830/840-1213
			Eaton	395 x 44.5 - 10 (Pre- Damper)	71/2-63032	81/2-7139	CV=Pressed Steel CT=Push CL=Single D/L=Diaphragm FLW =Flat	RBRG-000-395 With Collar	830/840-1214
CF 75									
75.300	07.92-98	RS222 M / 302HP	ZF 9S109	420 x 50.8 - 10	71/2-62001	81/2-42001	CV=Cast Iron CT=Push CL=Single D/L=Diaphragm FLW =Flat	RBRG-000-395 With Collar	830/840-1251
75.250 75.310 75.360	01.01- 01.01- 01.01-	PE 183C PE 228C PE 265C PR 183S PR 228S PR 265S	ZF 8S-151 ZF 16S-151	430 x 50.8 - 10 (Pre- Damper)	71/2-61102	81/2-7154	CV=Pressed Steel CT=Pull CL=Single D/L=Diaphragm FLW =Flat	RBRG-000-034 With Collar	830/840-2067
			ZF 9S-109 ZF 16S-109	395 x 44.5 - 10 (Pre- Damper)	71/2-63032	81/2-7139	CV=Pressed Steel CT=Push CL=Single D/L=Diaphragm FLW =Flat	RBRG-000-395 With Collar	830/840-1214
85									
85.300 85.330 85.360 85.400	-	WS 242 WS 268 WS 295	ZF	420 x 50.8 - 10	71/2-62001	81/2-42001	CV=Cast Iron CT=Push CL=Single D/L=Diaphragm FLW =Flat	RBRG-182-233 With Collar	830/840-1252
85 CF									
85 CF 340 85 CF 380 85 CF 430	02.98-12.00 02.98-12.00 02.98-12.00	XF 250M XF 280M XF 315M	ZF 16S-151	430 x 50.8 - 10 (Pre- Damper)	71/2-61102	81/2-7154	CV=Pressed Steel CT=Pull CL=Single D/L=Diaphragm FLW =Flat	RBRG-000-034 With Collar	830/840-2067
			Fuller	420 x 50.8 - 10	71/2-62001	81/2-42001	CV=Cast Iron CT=Push CL=Single D/L=Diaphragm FLW =Flat	RBRG-182-233 With Collar	830/840-1252
CF 85									
85.340 85.380 85.430 85.480	01.01- 01.01- 01.01- 01.01-	XE 250C XE 280C XE 315C XE 355C	ZF 16S-151 ZF 16S-181 ZF 16S-221 -	430 x 50.8 - 10 (Pre- Damper)	71/2-61102	81/2-7154	CV=Pressed Steel CT=Pull CL=Single D/L=Diaphragm FLW =Flat	RBRG-000-034 With Collar	830/840-2067

85.360 85.410 85.460 85.510	10.05- 10.05- 10.05- 10.05-	MX 265 MX 300 MX 340 MX 375	ZF ECOSPLIT 3	430 x 50.8 - 10 (Pre- Damper)	71/2-61102	81/2-7154	CV=Pressed Steel CT=Pull CL=Single D/L=Diaphragm FLW =Flat	RBRG-000-034 With Collar	830/840-2067
			ZF AS-TRONIC	430 x 50.8 - 10 (Pre- Damper)	71/2-61102	81/2-7154	CV=Pressed Steel CT=Pull CL=Single D/L=Diaphragm FLW =Flat	RBRG-000-493 With Collar ROLLER FORK	830/840-2080

				CLUTCH DIMENSIONS			REMARKS		
DAF									
95									
95.360	07.92-98	WS 266 364HP	ZF 16S-150	420 x 50.8 - 10	71/2-62001	81/2-42001	CV=Cast Iron CT=Push CL=Single D/L=Diaphragm FLW =Flat	RBRG-182-233 With Collar	830/840-1252
95.400 95.430	08.90-01.98 02.92-01.98	WS 315L XF 315M	Fuller	420 x 50.8 - 10	71/2-62001	81/2-42001	CV=Cast Iron CT=Push CL=Single D/L=Diaphragm FLW =Flat	RBRG-182-233 With Collar	830/840-1252
95.500	02.94-01.98	VF 373M	ZF 16S-221	430 x 50.8 - 10 (Pre- Damper)	71/2-61102	81/2-7154	CV=Pressed Steel CT=Pull CL=Single D/L=Diaphragm FLW =Flat	RBRG-000-034 With Collar	830/840-2067
95 XF									
95 XF 380 95 XF 430 95 XF 480 95 XF 530	01.97-09.02 01.97-09.02 01.97-09.02 01.97-09.02	XF 280M XF 315M VF 390M XE 390C XF 355M	ZF 16S-181	430 x 50.8 - 10 (Pre- Damper)	71/2-61102	81/2-7154	CV=Pressed Steel CT=Pull CL=Single D/L=Diaphragm FLW =Flat	RBRG-000-034 With Collar	830/840-2067
			Fuller	420 x 50.8 - 10	71/2-62001	81/2-42001	CV=Cast Iron CT=Push CL=Single D/L=Diaphragm FLW =Flat	RBRG-182-233 With Collar	830/840-1252
XF 95									
95.380 95.430 95.480 95.530	09.02-12.06 09.02-12.06 09.02-12.06 09.02-12.06	XE 250C XE 280C XE 315C XE 355C XE 390C	ZF16S-151 ZF16S-181 ZF16S-221	430 x 50.8 - 10 (Pre- Damper)	71/2-61102	81/2-7154	CV=Pressed Steel CT=Pull CL=Single D/L=Diaphragm FLW =Flat	RBRG-000-034 With Collar	830/840-2067
XF 105									
105.410 105.460 105.510	10.05- 10.05- 10.05-	MX 300 MX 340 MX 375	ZF 16S-2020 ZF 16S-2220	430 x 50.8 - 10 (Pre- Damper)	71/2-61102	81/2-7154	CV=Pressed Steel CT=Pull CL=Single D/L=Diaphragm FLW =Flat	RBRG-000-034 With Collar	830/840-2067
			ZF AS-TRONIC	430 x 50.8 - 10 (Pre- Damper)	71/2-61102	81/2-7154	CV=Pressed Steel CT=Pull CL=Single D/L=Diaphragm FLW =Flat	RBRG-000-493 With Collar ROLLER FORK	830/840-2080