

	CLUTCH DIMENSIONS			REMARKS		
DONGFENG									
WARRIOR									
7-125	-	Cumm 4BT	-	325 x 38.1 - 10	-	-	CV=Pressed Steel CT=Push CL=Single DL=Diaphragm FLW =Flat	-	-
14-160	-	Cumm 6BT	-	350 x 38.1 - 10	71/2-62019	81/2-35002	CV=Cast Iron CT=Push CL=Single DL=Lever FLW =Flat	RBRG-9538 Without Collar (Loose Bearing) ID = 55mm	830/840-1302
17-210	-	Cumm 6BTA	-	350 x 38.1 - 10	71/2-62019	81/2-35002	CV=Cast Iron CT=Push CL=Single DL=Lever FLW =Flat	RBRG-9538 Without Collar (Loose Bearing) ID = 55mm	830/840-1302
26-300 <i>Tipper</i>	-	Cumm 6CTA C300 20	Eaton	430 x 44.7 - 10	-	-	CV=Pressed Steel CT=Push CL=Single DL=Diaphragm FLW =Flat	-	-
26-300 <i>TT</i>	-	Cumm 6CTA C300 20	ZF	430 x 50.8 - 10 (Pre- Damper)	71/2-61102	-	CV=Pressed Steel CT=Pull CL=Single DL=Diaphragm FLW =Flat	RBRG-000-144 With Collar	-
KINGLAND									
DFL 420	-	dCi 420-30	ZF 16S-221	430 x 50.8 - 10	-	-	CV=Pressed Steel CT=Pull CL=Single DL=Diaphragm FLW =Flat	RBRG-000-034 With Collar	-